

AMENDMENTS TO SPECIFICATION

Please replace the paragraph beginning on page 15, line 14 and ending on line 21 with the following amended paragraph:

Referring now to FIG. 13, the assembly mandrel is shown. First dogs 211 and second dogs 212 are shown with the first dogs on fingers 1301. Depression 1302 for holding retainer tie ~~219~~223, and vent ports ~~217~~221 are shown for the piston section of the mandrel. Spacer 213, separating the expansion die from the upper cone is shown. Retainer tie 223 may be attached to the assembly mandrel, or may be fabricated as a part of the assembly mandrel.

Please replace the Abstract with the following Replacement Abstract:

A method is provided for providing a casing in a wellbore including placing a casing within the wellbore wherein the casing has a smaller outside diameter than a final inside diameter of the casing, placing an expandable mandrel within the casing, the expandable mandrel suspended from a drill string, converting the expandable mandrel to a first expansion diameter while the expandable mandrel is within the casing wherein the first expansion diameter is about the final inside diameter plus twice the thickness of the final casing; forcing the expanded mandrel through a lower portion of the casing while the expandable mandrel is of the first expansion diameter; converting the expandable mandrel to a second expansion diameter, wherein the second expansion diameter is about the final inside diameter, and forcing the expanded mandrel

through an upper portion of the casing while the expandable mandrel is of the second expansion diameter.